

# REO 9000™

## HIGH-CAPACITY BACKUP AND RECOVERY APPLIANCE WITH ProtectionPAC™ SOFTWARE



Whether you want to simply add disk to your backup strategy, increase the speed of backup and recovery, implement long-distance, cost-effective disaster recovery solutions, or reduce your reliance on tape in the backup process, the Overland Storage® REO 9000™ is the right solution. From an industry leader with over 23 years in the data protection business, the REO 9000 is the ideal choice for storage managers who want disk-speed data recovery, a cure for out-of-control backup windows and a method for improving the reliability of backup operations.

The REO 9000 is a shared-storage resource that improves the speed and efficiency of existing tape-based backup environments. Capable of storing up to 9.6 TB of data, it uses RAID 5 disk storage to increase backup reliability while providing near instantaneous recovery of files. Support for both iSCSI and Fibre Channel connections enables easy integration into existing SAN environments, while Overland's ProtectionPAC™ software provides the flexibility to create virtual storage devices as needed to make the best use of total available capacity.

ProtectionPAC software allows a user to configure the REO 9000 into any combination of virtual tape devices and disk LUNs. The ability to dynamically size virtual tape drives to the size of individual backup jobs further increases storage efficiency by eliminating the wasted space incurred when emulating fixed length tape cartridges. By storing tape images that are tailored to the size of the backup job, Overland allows users to access a significantly larger percentage of the available storage capacity.

Most important, the REO 9000 works with existing backup applications that were designed to support tape devices, providing users with a single backup catalog and a single media management system. This seamless compatibility allows easy deployment and integration into existing backup environments. As a result, REO 9000 users can quickly benefit from the ability to achieve rapid recovery of backup data from disk while continuing to rely on tape for long-term archival storage.

- UP TO 9.6 TB CAPACITY
- ProtectionPAC SOFTWARE
- DYNAMIC VIRTUAL TAPE DRIVE SUPPORT
- GbE AND FIBRE CHANNEL CONNECTIVITY
- SIMULTANEOUS DISK AND TAPE SUPPORT

### REO 9000 Features Include:

**High capacity**—the REO 9000 uses 400 GB SATA drives and scales up to 9.6 TB per unit to address high capacity backup applications.

**High-speed performance**—dual RAID controllers and dual high-speed connections to storage networks enable the REO 9000 to recover business-critical data at disk-speeds while helping to complete backups inside the backup window.

**Flexible connectivity**—utilizing dual GbE data ports with the option of adding dual 2 Gb Fibre Channel ports, the REO 9000 seamlessly integrates into existing storage networks.

**Increased data availability**—with hot-swap disk drives and power supplies, RAID 5 data protection and hot-sparing, the REO 9000 provides a high level of data availability.

**Broad platform support**—including Solaris, Microsoft® Windows®, and Linux, coupled with support for major third-party software applications, allows the REO 9000 to operate across a broad base of storage environments.

### ProtectionPAC Enterprise Solution Package:

**Flexible virtual device support**—provides the ability for each virtual device to be configured as a disk LUN or virtual tape drive, up to 64 total devices, enabling storage managers to implement a solution that most closely matches their current and future data protection requirements.

**Dynamic Virtual Tape**—provides the ability to dynamically size virtual tape drives to the size of individual backup jobs, providing higher usable capacity versus fixed length virtual tape devices.

**Browser based management**—provides proactive monitoring capability, event notification and remote management capability. The REO 9000 allows you to easily manage your backup and recovery process from a location that's convenient for you.

## REO 9000 SPECIFICATIONS

<b>SYSTEM STORAGE CAPACITY*</b> Raw Capacity RAID 5 Number of Disk Drives	9.6 TB 8.0 TB 24		
<b>STANDARD SOFTWARE FEATURES</b>	ProtectionPAC software, Dynamic Virtual Tape, disk virtualization, browser-based management, email alerts		
<b>STANDARD HARDWARE FEATURES</b>	19-inch rack-mount enclosure, hot-plug disk drives, redundant hot-plug power supplies, redundant cooling, enclosure alarms for power, fan and over-temperature conditions, dual RAID controllers, dual GbE data ports, 10/100 management port		
<b>EXTERNAL INTERFACES</b> Host Management Expansion	Two GbE Ports (RJ45); Two 2 Gb Fibre Channel ports (LC)—optional 10/100 Ethernet port (RJ45) Two UltraSCSI 320 ports		
<b>CONTROLLERS</b>	Dual RAID controllers		
<b>RAID SUPPORT</b>	JBOD, RAID 0, RAID 5 w/Hot Spare		
<b>DYNAMIC VIRTUAL TAPE/LUNS</b>	Any combination of Dynamic Virtual Tape Drives and LUNs, up to 64 total		
<b>POWER REQUIREMENTS</b> Voltage Frequency Current Power Cord Connector (US) Power Consumption	90 to 120 VAC, 200 to 240 VAC+/-10% 47 to 63 Hz 18A @ 115 VAC, 9A @ 230 VAC IEC 60320 C13 connectors, four per unit Steady state 1200 W; Peak 2000 W (fully populated)		
<b>ENCLOSURE</b> Dimensions (H x W x D) Vertical Rack Units Maximum Configuration Weight Shipping Weight	8.75 x 19.0 x 27.0 inches (22.2 x 48.3 x 68.6 cm) 5U rack units 130 pounds (59 kg) 160 pounds (73 kg)		
<b>ENVIRONMENTAL REQUIREMENTS</b> Humidity Temperature Altitude Shock Vibration	<table border="0"> <tr> <td> <b>OPERATING</b>                      20 to 80% non-condensing                      10 to 40° C                      -984 to 10,000 feet (-300 to 3,048m)                      10 G (11 ms half sine pulse)                      0.25 G swept sine                      (5–250–5 Hz) no errors                 </td> <td> <b>NON-OPERATING</b>                      10 to 95% non-condensing                      -40 v60° C                      -984 to 30,370 feet (-300 to 12,000 m)                      20 G (11 ms half sine pulse)                      1.0 G swept sine                      (5–250–5 Hz)                 </td> </tr> </table>	<b>OPERATING</b> 20 to 80% non-condensing 10 to 40° C -984 to 10,000 feet (-300 to 3,048m) 10 G (11 ms half sine pulse) 0.25 G swept sine (5–250–5 Hz) no errors	<b>NON-OPERATING</b> 10 to 95% non-condensing -40 v60° C -984 to 30,370 feet (-300 to 12,000 m) 20 G (11 ms half sine pulse) 1.0 G swept sine (5–250–5 Hz)
<b>OPERATING</b> 20 to 80% non-condensing 10 to 40° C -984 to 10,000 feet (-300 to 3,048m) 10 G (11 ms half sine pulse) 0.25 G swept sine (5–250–5 Hz) no errors	<b>NON-OPERATING</b> 10 to 95% non-condensing -40 v60° C -984 to 30,370 feet (-300 to 12,000 m) 20 G (11 ms half sine pulse) 1.0 G swept sine (5–250–5 Hz)		
<b>AGENCY APPROVALS</b>	UL/TUV, NRTL, CE, CUL (Canada), VCCI Class B/CISPR PUB 22 (Japan), TUV GS (Germany), BSMI (Taiwan)		
<b>INTEROPERABILITY</b>	Contact Overland Storage or visit <a href="http://www.overlandstorage.com">www.overlandstorage.com</a> for the most current iSCSI, Fibre Channel, and backup software compatibility matrices		

\* One TB equals one trillion bytes.

### WORLDWIDE HEADQUARTERS

4820 Overland Avenue  
 San Diego, CA 92123 USA  
 TEL 1-800-729-8725  
 1-858-571-5555  
 FAX 1-858-571-3664  
 EMAIL [sales@overlandstorage.com](mailto:sales@overlandstorage.com)

### UNITED KINGDOM (EMEA OFFICE)

Overland House  
 Ashville Way  
 Wokingham, Berkshire  
 RG41 2PL England  
 TEL +44 (0) 118-9898000  
 FAX +44 (0) 118-9891897  
 EMAIL [europe@overlandstorage.com](mailto:europe@overlandstorage.com)

### FRANCE OFFICE

Overland Storage  
 13 rue Camille Desmoulins  
 92441 Issy Les Moulineaux Cedex  
 France  
 TEL +33 (0) 1 58 04 25 50  
 FAX +33 (0) 1 58 04 26 36  
 EMAIL [europe@overlandstorage.com](mailto:europe@overlandstorage.com)

### GERMANY OFFICE

Humboldtstr. 12  
 85609 Dornach  
 Germany  
 TEL +49-89-94490-214  
 FAX +49-89-94490-414  
 EMAIL [europe@overlandstorage.com](mailto:europe@overlandstorage.com)

### ASIA PACIFIC REP. OFFICE

Level 44, Suntec Tower Three  
 8 Temasek Boulevard  
 Singapore 038988  
 TEL +65 6866 3848  
 FAX +65 6866 3838  
 EMAIL [asia@overlandstorage.com](mailto:asia@overlandstorage.com)

[WWW.OVERLANDSTORAGE.COM](http://WWW.OVERLANDSTORAGE.COM)